



White MountainTM

Wet Look LacquerTM

Clear Protection for Concrete, Masonry, Tile, and Stone Surfaces

Specifications

DESCRIPTION:

Wet Look Lacquer creates a deep penetrating barrier coating to protect and beautify surfaces by bringing out the rich colors of concrete and masonry surfaces, effectively giving substrates the appearance of a wet surface. **Wet Look Lacquer** can also be used as a joint sand stabilizer for interlocking pavers. Utilizing cutting edge components and microtechnology, **Wet Look Lacquer** provides the ultimate deep penetration, protection and enhancement for all concrete, masonry, and stone surfaces.

USE:

Wet Look Lacquer is ideal for use on:

- manufactured and natural stone
- colored and stamped concrete
- exposed aggregate concrete
- interlocking concrete pavers
- Mexican tile - saltillo
- masonry brick
- natural slate.

ADVANTAGES:

- Resistant to oil and grease stains
- Interior and exterior use
- Excellent adhesion
- UV resistant bond
- Water repellent
- Easy to apply
- Recoatable

LIMITATIONS:

- Not recommended for pre-sealed surfaces or non-porous surfaces such as ceramic tile, marble, granite, porcelain and terrazzo.

Properties

VOC: [minus exempt solvents & water] ... 347 g/l – (2.90 lbs/gal)

FLASH POINT: [setaflash].....>-4° F

APPEARANCE:

Wet clear

Dry clear; gloss

ODOR: strong solvent

WEIGHT PER GALLON: [average] 7.3 lbs

PACKAGE VISCOSITY: [#2 Zahn] 19 sec

SOLIDS: [average]

By Weight 23.4 ± 1%

By Volume 18.4 ± 1%

COVERAGE: [approximate]

Porous Surface 50-200 sq ft/gal

Dense Surface 200-400 sq ft/gal

For exact coverage rates, a measured quantity to proper saturation over a known area will provide a square foot coverage rate for a specific job.

DRY SCHEDULE: [at 50% RH and 1 mil DFT]

	50° F	60° F	75° F
Dry to Touch	2 hrs	90 mins	30 mins
Rainproof/Cured	12 hrs	12 hrs	12 hrs

ORDER CODE: W1-02OX

PACKAGING:

Four 1 gallon F style metal cans per case

5 gallon metal pails

Wet Look Lacquer™

Clear Protection for Concrete, Masonry, Tile, and Stone Surfaces

Application Data

SURFACE PREPARATION:

- Before use, thoroughly test this product on a sample to assure performance and appearance.
- Surface must be completely clean and dry to the touch.
- Remove all dirt, wax, old paints or sealers with appropriate cleaner, chemical stripper or abrasive blasting. If muriatic acid has been used, the surface must be flushed with clean water and neutralized with a pH neutralizer such as **White Mountain Jobsite Cleaner**. We do not recommend muriatic acid for cleaning concrete as it may discolor the surface, etch the concrete, and is hazardous to use.
- After cleaning, allow surface to dry 24 hours prior to sealer application.
- Allow new concrete to cure for at least 14 days before application.

APPLICATION:

Wet Look Lacquer can be applied with a natural sponge, brush, roller, or most types of spray equipment. One coat will seal and protect the surface, while additional coats will give more protection and higher gloss. If a second coat is desired, apply as soon as first coat is dry to the touch.

Spraying is the preferred method of application. For small areas, a pump-up metal garden sprayer is convenient, however, regularly clean spray tip with solvent and a stiff brush.

Applicator:

- Brush.....natural bristle brush
- Roller.....1/4" to 3/8" nap solvent resistant roller
- Airless sprayer tip size0.013" - 0.015"

Porous Surfaces:

Example: paver brick, flagstone, clay tile, etc. Generally, one coat will provide complete protection. A second coat will provide added protection. Apply second coat after first coat is dry to touch. To strengthen old, porous and crumbling surfaces, additional applications may be required.

Dense Surfaces:

Example: slate, limestone, concrete tile, etc. One light to moderate coat supplies complete protection and a high gloss finish. Additional coats are not recommended for dense surfaces. Not recommended for glazed tile.

Do not apply **Wet Look Lacquer** during inclement

weather or in direct sunlight when temperature exceeds 80°F. Do not apply to wet or damp surfaces. Air and surface temperature should be between 50°F and 80°F for 24 hours following application.

IMPORTANT NOTE:

Do not over apply. Excess sealer should not be allowed to pool or puddle.

Water Penetration Test:

Sprinkle a small amount of water on the sealed surface. If water penetration occurs or if water does not bead up on surface, apply additional sealer. This test should be performed after each applied coat.

CLEANUP: acetone or xylene

MAINTENANCE:

After cured, pressure wash, hose, or mop. Periodic cleaning with **White Mountain Jobsite Cleaner** is recommended.

TO REMOVE: acrylic stripper or abrasive blasting

Health & Safety

WARNING:

LIQUID CONTACT WITH EYE AND SKIN MAY CAUSE IRRITATION. DO NOT INGEST. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. If spillage has occurred, absorb and dispose of according to local regulations.

FIRST AID:

Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If swallowed, seek medical attention immediately. DO NOT induce vomiting.

THIS PRODUCT IS FOR PROFESSIONAL USE ONLY.

KEEP THIS PRODUCT OUT OF THE REACH OF CHILDREN.

Shipping & Handling

SHIPPING DESCRIPTION: [CFR 49]

- Ground, Air, Vessel Paint, 3, UN1263, PG II
- Required Label FLAMMABLE LIQUID
- Required Marking PAINT UN1263

IMDG PACKAGING:

FLAMMABLE LIQUID, class 3.2, UN1263, II

IMDG STOWAGE: Category B

UNIFORM FIRE CODE: [CFR 29] CLASS 1-B

STORAGE TEMPERATURE: 35°F - 110°F

SHELF LIFE: [warranted] 1 YEAR

HMIS RATINGS: H - 2; F - 3; R - 0; PP - H

WARRANTY: The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control. (01/09)