	Μ	Α	Τ	Ε	R	I	Α	L	S	Α	F	Ε	Τ	Y	D	Α	Τ	Α	S	Η	Ε	Ε	Τ	
-																								-

PRODUCT NAME : CLASSIC Oil Carbon Black

IDENTIFICATION NUMBER: D200 DATE PRINTED: 12/03/02

PRODUCT USE/CLASS :

SUPPLIER: MANUFACTURER:

Triangle Coatings, Inc. Triangle Coatings, Inc. 1930 Fairway Drive 1930 Fairway Drive

San Leandro, CA 94577-5631 San Leandro, CA 94577-5631 800-895-8000 (8:00am-5:00pm) 800-895-8000 (8:00am-5:00pm)

CHEMTREC 24HR EMERGENCY TELEPHONE CHEMTREC 24HR EMERGENCY TELEPHONE 800-424-9300 800-424-9300

PREPARER: NF, PHONE: , PREPARE DATE: 01/09/01

| SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS | WT/WT % ITEM ------ CHEMICAL NAME ------ CAS NUMBER LESS THAN

No Hazardous Materials are Contained in this Product

(See Section 16 for abbreviation legend)

|-----|
| SECTION 3 - HAZARDS IDENTIFICATION |

*** EMERGENCY OVERVIEW ***: Harmful if swallowed. Causes eye irritation.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause irritation including pain, tearing or reddening accompanied by stinging sensation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Vapors may cause irritation of the respiratory tract.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: None.

(Continued on Page 2)

	Product:	D200		P:	reparatio	on Date:	01/09/01	Pa	ige 2
	=========		=======	===	=======				:====
			SECTION	3 -	HAZARDS	IDENTIF:	ICATION		
١	=========	======	=======	===	======				=====

PRIMARY ROUTE(S) OF ENTRY: Unknown

		=====
	SECTION 4 - FIRST AID MEASURES	
1	I ====================================	=====

FIRST AID - EYE CONTACT: Flush with water for 15 minutes while holding eye lids open. Get medical attention.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

	SECTION 5 - FIRE FIGHTING MEASURES
I	

FLASH POINT: N.A.

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE:

EXTINGUISHING MEDIA: Unknown

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid spreading burning liquid with water used for cooling purposes. Cool fire-exposed containers with water.

=======================================
SECTION 6 - ACCIDENTAL RELEASE MEASURES
=====================================

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Absorb spill with suitable absorbent material, then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section) If large spill, dike area and call spill response team. Notify appropriate state and local agencies. Wear protective equipment during cleanup (refer to Section 8).

(Continued on Page 3)

	Product: I	5200	Pre	eparation	Date	e: 01/09/01	Pa	ge .	3
	=========		:====		-===			===:	==
		SECTION	7 -	HANDLING	AND	STORAGE			
ı	=========		:====		-===			===:	==

HANDLING: Wash thoroughly after handling. Avoid spontaneous combustion of contaminated rags and other easily ignitable accumulations (such as spray booth residues) by immediate immersion in water. Emptied containers may retain residues.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Do not weld, heat or drill on or near container; even emptied containers can contain explosive vapors.

```
| SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION |
```

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Respiratory protection may be required if material is used in poorly ventilated areas or if material is sprayed or heated.

SKIN PROTECTION: General use of chemical resistant gloves are recommended to protect the skin from drying and irritation.

EYE PROTECTION: Eye protection is recommended.

OTHER PROTECTIVE EQUIPMENT: If repeated or prolonged skin contact or contamination is likely, protective clothing should be worn. Eye wash fountain and safety shower should be available.

HYGIENIC PRACTICES: Always wash hands before eating, drinking, or smoking. Remove contaminated clothing and wash before reuse.

```
|-----|
| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES |
```

BOILING RANGE : N.A. VAPOR DENSITY : Is lighter than air

ODOR : ODOR THRESHOLD :

APPEARANCE : EVAPORATION RATE: Is slower than Butyl

SOLUBILITY IN H2O: Acetate

FREEZE POINT : SPECIFIC GRAVITY: 1.0060

VAPOR PRESSURE : pH @ 0.0 % : PHYSICAL STATE : VISCOSITY :

VOLATILE BY VOLUME: 2.2%

COEFFICIENT OF WATER/OIL DISTRIBUTION:

(See Section 16 for abbreviation legend)

(Continued on Page 4)

Product: D200	Preparation Date: 01/09/01	Page 4
SI	ECTION 10 - STABILITY AND REACTIVITY	======== =========
CONDITIONS TO AVOID	: Avoid heat, sparks, and open flame.	'
INCOMPATIBILITY: A	oid contact with strong oxidizing agents.	
	TION PRODUCTS: Thermal decomposition in the monoxide and/or carbon dioxide.	presence of
HAZARDOUS POLYMERIZA	ATION: Will not occur under normal condition	S.
STABILITY: This prod	duct is stable under normal storage conditio	ns.
SI	ECTION 11 - TOXICOLOGICAL PROPERTIES	i
No product or compon	nent toxicological information is available.	
TOXICOLOGICAL INFORM	MATION: No Information.	
	SECTION 12 - ECOLOGICAL INFORMATION	į
water and air qualif	ION: Refer to local, county, state and fede ty regulations. BECTION 13 - DISPOSAL CONSIDERATIONS	=======
DISPOSAL METHOD: I: to be treated as has ignitability as defi Disposal of this man packaging, and reco:	E discarded, this material and its container cardous waste based on the characteristics of ined under Federal RCRA regulations (40 CFR terial may require compliance with applicabled keeping standards. Extreme care should be isposed of only in a facility permitted for	s may have f 261). e labeling, taken to
SEC	TION 14 - TRANSPORTATION INFORMATION	į
	nformation is available.	=======================================
	SECTION 15 - REGULATORY INFORMATION	======= -========
U.S. FEDERAL REGULA	TIONS: AS FOLLOWS -	
OSHA: Non-hazardous 1910.1200)	by definition of Hazard Communication Stand	ard (29 CFR

(Continued on Page 5)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN No SARA Section 313 components exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

|=======| | SECTION 16 - OTHER INFORMATION | |========|

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 01/05/01

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.16 lbs/gal, 19 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,

N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.
