



# White Mountain™ Wet Look OX™

**Clear Protection for Concrete, Masonry, Tile, and Stone Surfaces**

## SPECIFICATIONS

### DESCRIPTION:

**Wet Look OX** creates a deep penetrating barrier coating to protect and beautify surfaces by bringing out the rich colors of concrete and masonry surfaces. The original, high gloss formula effectively gives substrates the appearance of a wet surface, while the low gloss version brings out the vibrance and depth of substrates without the high gloss finish. **Wet Look OX** can also be used as a joint sand stabilizer for interlocking pavers. Utilizing cutting edge components and micro-technology, **Wet Look OX** provides the ultimate deep penetration, protection and enhancement for all concrete, masonry, and stone surfaces.

### USE:

**Wet Look OX** is ideal for use on:

- manufactured and natural stone
- colored and stamped concrete
- exposed aggregate concrete
- interlocking concrete pavers
- Mexican tile - saltillo
- masonry brick
- natural slate
- marble and granite\*

[\*Marble and granite vary in porosity. Some marbles are extremely moisture sensitive; all are acid sensitive. Some granites will rust and fade when used outdoors. Sealing marble and granite is strongly recommended to avoid staining.]

Product results will vary by substrate and application method. **It is the user's responsibility to determine the suitability and performance of this product for their application.**

### ADVANTAGES:

- Extremely low VOC
- Resistant to oil and grease stains
- Interior and exterior use
- Excellent adhesion
- UV resistant bond
- Water repellent
- Easy to apply
- Recoatable

### LIMITATIONS:

- Not recommended for pre-sealed surfaces or non-porous surfaces such as ceramic tile, porcelain and terrazzo.

## PROPERTIES

**VOC:** [minus exempt solvents & water] ..... 347 g/l – (2.90 lbs/gal)

**FLASH POINT:** [setaflash] ..... >-4° F

### APPEARANCE:

Wet ..... clear

Dry ..... clear; gloss/low-gloss

**ODOR:** ..... strong solvent

**WEIGHT PER GALLON:** [average] ..... 7.3 lbs

**PACKAGE VISCOSITY:** [#2 Zahn] ..... 18-22 sec

### SOLIDS:

By Weight ..... 23.4 ± 1%

By Volume ..... 18.4 ± 1%

### COVERAGE:

Porous Surface ..... 50-200 sq ft/gal

Dense Surface ..... 200-400 sq ft/gal

For more exact coverage rates, apply measured quantities of product to 1 square foot of substrate. Repeat until saturation obtained. Saturation obtained when material begins to pool on surface.

### DRY SCHEDULE:

	50° F	60° F	75° F
<b>Dry to Touch</b>	2 hrs	90 mins	30 mins
<b>Rainproof/Cured</b>	12 hrs	12 hrs	12 hrs

### ORDER CODE:

Wet Look OX, Gloss ..... W1-02

Wet Look OX, Low Gloss ..... W1-02M

### PACKAGING:

Four 1 gallon F style metal cans per case

5 gallon metal pails

# Wet Look OX™

## Clear Protection for Concrete, Masonry, Tile, and Stone Surfaces

### APPLICATION DATA

#### SURFACE PREPARATION:

- Before use, thoroughly test this product on a sample to assure performance and appearance.
- Surface must be completely clean and dry to the touch.
- Remove all dirt, wax, old paints or sealers with appropriate cleaner, chemical stripper or abrasive blasting. If muriatic acid has been used, the surface must be flushed with clean water and neutralized with a pH neutralizer such as **White Mountain Jobsite Cleaner**. We do not recommend muriatic acid for cleaning concrete as it may discolor the surface, etch the concrete, and is hazardous to use.
- After cleaning, allow surface to dry 24 hours prior to sealer application.
- Allow new concrete to cure for at least 14 days before application.

#### APPLICATION:

**Wet Look OX** can be applied with a natural sponge, brush, roller, or most types of spray equipment. One coat will seal and protect the surface, while additional coats will give more protection and higher gloss. If a second coat is desired, apply as soon as first coat is dry to the touch.

For small areas, use an appropriate handheld sprayer to apply all solvent based coatings. Consult your local equipment supplier for recommendations. Do not allow coating to dry on spray tip. If this occurs, soak the tip in the recommended cleaning agent.

#### Applicator:

Brush ..... natural bristle brush  
 Roller ..... ¼" to ¾" nap solvent resistant roller  
 Airless sprayer tip size ..... 0.013" - 0.015"

#### Porous Surfaces:

Example: paver brick, flagstone, clay tile, etc. Generally, one coat will provide complete protection. Apply one generous, even coat to saturate surface. A second coat will provide added protection. Apply second coat after first coat is dry to touch. To strengthen old, porous and crumbling surfaces, additional applications may be required.

#### Dense Surfaces:

Example: slate, limestone, concrete tile, etc. One light to moderate coat supplies complete protection and a high gloss finish. Additional coats are not recommended for dense surfaces. Not recommended for glazed tile.

#### Application Caution:

Cover all plants, trees, grasses, and shrubs to protect from overspray. If overspray occurs, wash off with water immediately. Mask areas that may be affected by overspray.

Do not apply **Wet Look OX** during inclement weather or in direct sunlight when temperature exceeds 80° F. Do not apply to wet or damp surfaces. Air and surface temperature should be between 50° F and 80° F for 24 hours following application.

#### IMPORTANT NOTE:

Do not over apply. Excess sealer should not be allowed to pool or puddle.

#### Water Penetration Test:

Sprinkle a small amount of water on the sealed surface. If water penetration occurs or if water does not bead up on surface, apply additional sealer. This test should be performed after each applied coat.

#### CLEANUP: ..... acetone or PCBTF MAINTENANCE:

After cured, pressure wash, hose, or mop. Periodic cleaning with **White Mountain Jobsite Cleaner** is recommended.

#### TO REMOVE: ..... acrylic stripper or abrasive blasting

### HEALTH & SAFETY PRECAUTIONS

#### WARNING:

**FLAMMABLE LIQUID AND VAPOR.** May be harmful if swallowed or inhaled. Vapor may affect the brain or nervous system causing dizziness, headache, or nausea and can cause nose and throat irritation. Liquid contact with eye and skin causes irritation. Keep away from sparks, heat, or open flame. Use with adequate ventilation. Avoid breathing of vapor. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. Wear an appropriately fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor levels are below applicable limits. Keep container closed when not in use. If spillage occurs, absorb and dispose of according to local regulations.

**Contains:** Acetone, CAS#67-64-1; Aromatic Hydrocarbon Mixture, CAS#64742-95-6; 2-Butoxyethanol, CAS#111-76-2; Parachlorobenzotrifluoride, CAS#98-56-6; Butyl Benzyl Phthalate, CAS#85-68-7.

#### FIRST AID:

Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If swallowed, seek medical attention immediately. DO NOT induce vomiting.

#### CA PROPOSITION 65:

This product contains a chemical known to the State of California to cause birth defects, or other reproductive harm.

**THIS PRODUCT FOR PROFESSIONAL USE ONLY.  
 KEEP OUT OF THE REACH OF CHILDREN.**

### SHIPPING & HANDLING

#### SHIPPING DESCRIPTION: [CFR 49]

**Ground, Air, Vessel** ..... Paint, 3, UN1263, PG II  
 Required Label ..... FLAMMABLE LIQUID  
 Required Marking ..... PAINT UN1263

#### IMDG PACKAGING:

FLAMMABLE LIQUID, class 3.2, UN1263, II

#### IMDG STOWAGE: ..... Category B

**UNIFORM FIRE CODE:** [CFR 29] ..... CLASS 1-B

**STORAGE TEMPERATURE:** ..... 35°F - 110°F

**SHELF LIFE:** [warranted] ..... 1 YEAR

**HMIS RATINGS:** ..... H - 2; F - 3; R - 0; PP - H

**WARRANTY:** The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control.

Product Data Sheets are periodically updated to reflect new information relating to the product. It is important to obtain the most recent Product Data Sheet for the product being used before application. WMW102-10/12-006

TRIANGLE COATINGS, INC. 4763 Bennett Drive, Livermore, CA 94551-4804 • Tel: 925-583-0800 • Fax: 925-583-0880 • [www.tricoat.com](http://www.tricoat.com)