

Wood Cleaner

Multi-Purpose Cleaner for Wood Surfaces

SPECIFICATIONS

DESCRIPTION:

Wood Cleaner is designed specifically to clean wood decks, fences and siding. It stops new wood from greying or darkening, and returns luster to old wood. **Wood Cleaner** refreshes wood damaged by sun exposure and water from rain and sprinklers. This cleaner will outperform any of its type, aggressively extracting mildew, mold, algae and tannin from most wood surfaces. Developed from a water based concentrate, it can be diluted with up to 5 parts water, making it highly cost effective. Dilution rate determines cleaning power.

USE:

Wood Cleaner can be used for any exterior, unpainted wood surface.

Wood Cleaner is ideal for use on:

- · decks and fences
- siding and panelling
- trellises and latticework
- exterior awning frames
- exposed wood shutters

Product results will vary by substrate and application method. It is the user's responsibility to determine the suitability and performance of this product for their application.

ADVANTAGES:

- · Very effective on tannin and mildew
- Biodegradable and safe
- Water based formula
- Concentrated
- Cost effective

LIMITATIONS:

Not a paint or efflorescence remover

PROPERTIES

TRIANGLE COATINGS, INC. Sales: 925-583-0800 www.tricoat.com



Wood Cleaner Multi-Purpose Cleaner for Wood Surfaces

APPLICATION DATA

SURFACE PREPARATION:

- Before use, thoroughly test this product on a sample to assure performance and appearance.
- Always test on a small area to be sure cleaner is not removing or damaging surrounding surface coating or sealer.
- Water down surrounding plants, ground cover and grass to avoid temporary discoloration.
- Remove excess dirt and debris from surface to be cleaned.

APPLICATION:

- Shake thoroughly before mixing or using.
- Always add solution to water, then stir or mix. Adding water to solution will result in foam and bubble formation.
- Mix with up to 5 parts water and apply to surface with sprayer or other manual method. If not sure which dilution to use, start with a light solution and add cleaner until ideal results are met.
- Let stand 2 to 5 minutes; do not allow to dry.
- Scrub surface with a stiff brush or broom.
- Rinse thoroughly or until foaming stops.
- If cleaner dries on surface, reapply and continue.
- Allow surface to dry completely before applying sealers, coatings, or paint.

DO NOT MIX THIS PRODUCT WITH BLEACH

Wood Cleaner is incompatible with chlorine bleaches, ammonia, and most other cleaners. Do not use on metal.

Application Caution:

Cover all plants, trees, grasses, and shrubs to protect from overspray. If overspray occurs, wash off with water immediately. Mask areas that may be affected by overspray.

RECOMMENDED DILUTION RATES:

- 1:1.... Heavily soiled, ground in dirt, deep seeded and/or old stains
- 3:1 Moderate stains and general cleaning
- 5:1 Mild or new stains, mild to moderate soiling

Use the same dilution ratio with a pressure washer (900 psi maximum) or automatic floor scrubber. If pressure washer or scrubber is used, hand scrubbing is not necessary. For extremely heavy duty cleaning, use **Wood Cleaner** without dilution.

For best results, use warm water if possible.

CLEANUP: flush with clean water

HEALTH & SAFETY PRECAUTIONS

WARNING:

CONTAINS OXALIC ACID. LIQUID CONTACT WITH EYE AND SKIN MAY CAUSE IRRITATION. DO NOT INGEST. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. If spillage has occurred, absorb and dispose of according to local regulations. **Contains:** Ethanoioic Acid, CAS#144-62-7; Ethoxylated Nonylphenol, CAS#9016-45-9; Mineral Oil Wax Hyrdophobic Silica.

FIRST AID:

Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If swallowed, seek medical attention immediately. DO NOT induce vomiting.

CA PROPOSITION 65:

This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

THIS PRODUCT FOR PROFESSIONAL USE ONLY. KEEP OUT OF THE REACH OF CHILDREN.

SHIPPING & HANDLING

SHIPPING DESCRIPTION: [CFR 49]	
Ground, Air, Vessel Non Regulated Material	
Required Label & Marking	Not Required
IMDG PACKAGING & STOWAGE:	Not Regulated
UNIFORM FIRE CODE: [CFR 29]	Non Combustible
STORAGE TEMPERATURE:	45°F - 90°F
KEEP WATER BASED PRODUCTS FROM FREEZING	
SHELF LIFE: [warranted]	1 YEAR
HMIS RATINGS: H - 1; F - 0; R - 0; PP - H	

WARRANTY: The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonable to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control.

Product Data Sheets are periodically updated to reflect new information relating to the product. It is important to obtain the most recent Product Data Sheet for the product being used before application. WMW204-10/12-005 TRIANGLE COATINGS, INC. 4763 Bennett Drive, Livermore, CA 94551-4804 • Tel: 925-583-0800 • Fax: 925-583-0880 • www.tricoat.com