

**TRIANGLE ARCHITECTURAL****Pure & Natural™****Premium 100% Acrylic Interior Latex Paint****Specifications****DESCRIPTION:**

**Pure & Natural** is a 100% acrylic water based interior finish that has extreme scrub resistance. **Pure & Natural** is unmatched in performance and aesthetics providing maximum durability and effectively covering hairline cracks. **Pure & Natural** contains very low VOC and is virtually odorless. This product was formulated to meet the demands of professional painters' requirements. **Pure & Natural** has a smooth consistency, is drip and splatter resistant, and easy to apply. This product protects from mold growth and resists water penetration, providing a long lasting mildew and stain resistant surface. **Pure & Natural** is available in a broad range of colors and can be tinted to match most custom colors. Contact your Triangle Coatings representative for more information on color selections.

**USE:**

**Pure & Natural** is designed for use as an architectural finish for interior surfaces. It can also be used for maintenance or touch-up painting.

**Pure & Natural** is ideal for use on properly prepared:

- interior residential walls, ceilings, and trim
- dining rooms and living rooms
- bedrooms and bathrooms
- office suites
- hotel rooms
- hospital rooms
- public buildings
- schools and day care centers

**ADVANTAGES:**

- Elegant flat or eggshell finish
- Odorless
- Low VOC
- Fast drying
- Drip and splatter resistant
- 100% Washable
- Easy water cleanup
- Custom colors available

**LIMITATIONS:**

- Low VOC requires use of factory tinted colors; store colorants may contain organic solvents
- Not for consumption; DO NOT INGEST
- Not recommended for traffic bearing surfaces
- Not recommended for use in wet or chemical environments or surfaces subject to abrasion
- Not recommended for spray acoustic texture or unprimed acoustic tile

**Properties**

**VOC:** [as packaged] ..... <35 g/l – (0.29 lbs/gal)

**FLASH POINT:** [setaflash]..... none

**APPEARANCE:** [Gloss @ 60°]

Eggshell ..... 15-20

Flat ..... 2-5

**WEIGHT PER GALLON:** [average] ..... 11.67 lbs

**PACKAGE VISCOSITY:** ..... 90-100 KU

**SOLIDS:** [average]

By Weight ..... 52 ± 2%

By Volume ..... 37 ± 2%

**COVERAGE:** [average]

Theoretical at 1 mils DFT ..... 593 sq ft/gal

Recommended DFT ..... 1.5-2.0 mils

**DRY SCHEDULE:** [at 50% RH and 2 mils DFT]

	50° F	77° F
<b>Dry to Touch</b>	2 hrs	30 mins
<b>Recoat</b>	4-5 hrs	2-3 hrs
<b>Full Cure</b>	12 hrs	8 hrs

After 1 week, light sanding may be necessary if recoating is required.

**COLOR AVAILABILITY:**

**Pure & Natural** is packaged as white. Any architectural color can be made with minimum order. Pastel and midtone colors can be factory or store tinted. VOC level may be impacted by the colorant; factory tinted colors retain a low VOC level.

**ORDER CODE:** ..... 70 + gloss designator + color #  
Individual products are identified using the two digit product series number, followed by the letter designating gloss, followed by the color or base number.

Ex: 70F700 is Pure & Natural Flat, White

F = Pure & Natural Flat

E = Pure & Natural Eggshell

**PACKAGING:**

Six 1 quart cans per case

Four 1 gallon cans per case

5 gallon pails

55 gallon drums (available upon request)

250 gallon totes (available upon request)

# Pure & Natural™

## Premium 100% Acrylic Interior Latex Paint

### Application Data

#### SURFACE PREPARATION:

- Before use, thoroughly test this product on a sample to assure correct color, appearance, and performance.
- Remove all loose or flaking paint and contaminants. Repair cracked or spalled masonry. Replace rotted or decaying wood and reset nails. Caulk all open seams that may allow moisture into wood surface.
- Surfaces must be completely dry and free of contaminants. Ex: oil, wax, silicone, chalk, and efflorescence.
- Both surface and ambient temperatures must be above 50°F (10°C) and remain above 50°F (10°C) for four hours after application. Relative humidity should be below 85%.

#### PRIMING:

**Pure & Natural** finishes are designed for use over **281 AllPrime**. However, moisture sensitive building materials or those with surface defects may require special primers. Consult your Triangle Coatings representative for primer recommendations.

#### APPLICATION:

Apply **Pure & Natural** by brush, roller, or airless spray. Use a brush to cut in, touch up, paint deeply recessed areas, paint most trim, and paint smooth siding. Masonry and plywood should be rolled or back rolled if sprayed. Airless spray is recommended on overhangs and smooth siding.

#### Brush:

Bristles: ..... nylon polyester  
Apply liberally, work into recesses, scrubbing or stippling if necessary.

#### Roller:

Cover:..... 3/8" lint free synthetic nap  
Apply liberally in X or V pattern. Roll over and force into depressions for uniform coverage.

#### Airless:

Fluid Tip:..... .013 - .015"  
Fluid Pressure: ..... 1700 - 1800 psi  
½ gpm or larger pumps are recommended.

Surfaces must be dry and protected from all moisture until rainproof, as per dry schedule.

**THINNING:** ..... none

**CLEANUP:** ..... water  
Clean tools and hands with soapy water.

### Health & Safety

#### WARNING:

LIQUID CONTACT WITH EYE AND SKIN CAUSES IRRITATION. DO NOT INGEST. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. If spillage has occurred, absorb and dispose of according to local regulations.

#### FIRST AID:

Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If swallowed, seek medical attention immediately. DO NOT induce vomiting.

**KEEP THIS PRODUCT OUT OF THE REACH OF CHILDREN.**

### Shipping & Handling

**SHIPPING DESCRIPTION:** [CFR 49]  
**Ground, Air, Vessel** ..... Non Regulated Material  
**Required Label & Marking** ..... Not Required  
**IMDG PACKAGING:** ..... Not Required  
**IMDG STOWAGE:** ..... Not Regulated  
**UNIFORM FIRE CODE:** [CFR 29] ..... None  
**STORAGE TEMPERATURE:** ..... 120° F max  
**SHELF LIFE:** [warranted] ..... 1 YEAR  
**HMIS RATINGS:** ..... H - 1; F - 0; R - 0; PP - B

**WARRANTY:** The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control. (03/09)