

**TRIANGLE TUB & TILE****Bubble Gum Scent****Odor Mask for Liquid Porcelain Finishes****Specifications****DESCRIPTION:**

**Bubble Gum Scent** and all products of the **Liquid Porcelain Refinishing Systems** were designed specifically for the tub and tile refinishing industry. **Bubble Gum Scent** is added to the mixed system to minimize solvent odor and provide a pleasant odor experience for people in the vicinity of the jobsite.

**USE:**

**Bubble Gum Scent** is used to provide a pleasant odor by masking objectionable solvent odors when **Liquid Porcelain 505 Series** is used in a resurfacing process.

**ADVANTAGES:**

- Designed specifically for Tub and Tile Refinishing
- Provides a pleasant odor replacing possible unpleasant solvent odors
- Can be added to **Liquid Porcelain** without affecting gloss, cure, color, or durability
- Very cost effective. Typical use is less than one half ounce per quart

**LIMITATIONS:**

- For professional use only
- Do not ingest

**Properties**

**VOC:** [as packaged] ..... 8.6 lbs/gal (100%)

**FLASH POINT:** [setaflash] ..... 122° F

**APPEARANCE:**

Wet ..... Amber Liquid

**SPECIFIC GRAVITY** ..... 1.03

**PACKAGE VISCOSITY:** ..... 1 Zahn

**SOLIDS:**

By Weight ..... <1%  
By Volume ..... <1%

**DRY SCHEDULE:** ..... Not Applicable

**ORDER CODE:** ..... AX04

**PACKAGING:** ..... one quart F-style can

**Shipping & Handling****SHIPPING DESCRIPTION:** [CFR 49]

**Ground, Air, Vessel** .... Paint, 3, UN1263, PG II  
Required Label ..... FLAMMABLE LIQUID  
Required Marking ..... PAINT UN1263

**IMDG PACKAGING:**

FLAMMABLE LIQUID, Class 3.2, UN1263, II

**IMDG STOWAGE:** ..... Category B

**UNIFORM FIRE CODE:** [CFR 29] ..... CLASS I-B

**STORAGE TEMPERATURE:** ..... 100° F max

**SHELF LIFE:** [warranted] ..... 1 YEAR

**HMIS RATINGS:** ..... H - 1; F - 2; R - 0; PP - G

# Bubble Gum Scent

## Odor Mask for Liquid Porcelain Finishes

### Application Data

#### REQUIREMENTS:

- Follow directions for **Liquid Porcelain** preparation.

#### FILM DEVELOPMENT & THICKNESS:

**Bubble Gum Scent** is used at extremely low levels. Use only enough to achieve desired odor masking. Excess material may slow solvent release and therefore retard cure. Typical substrates are tub and tile surfaces such as ceramic, porcelain, glazed or unglazed tile and various metals. Actual application rates vary but use approximately one ounce per quart of **Liquid Porcelain**.

#### MIXING/THINNING:

Use approximately one ounce (two capfuls) of **Bubble Gum Scent** per quart of **Liquid Porcelain** Part A. Then follow manufacturer's recommendations for thinning and mixing **Liquid Porcelain**.

#### APPLICATION:

Follow manufacturer's recommendations for spraying **Liquid Porcelain**.

#### CLEANUP:

Clean up spilled **Bubble Gum Scent** with soap and water.

### Health & Safety

#### WARNING:

FLAMMABLE LIQUID AND VAPOR. MAY BE HARMFUL IF SWALLOWED OR INHALED. VAPOR MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA AND CAN CAUSE NOSE AND THROAT IRRITATION. LIQUID CONTACT WITH EYE AND SKIN CAUSES IRRITATION. Contains isocyanates. Keep away from sparks, heat, and open flame. Use with adequate ventilation. Avoid breathing of vapor. Avoid contact with eyes, skin and clothing. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Keep container closed when not in use. If spillage occurs, absorb and dispose of according to local regulations.

#### FIRST AID:

Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If inhaled, remove to fresh air. If swallowed, seek medical attention immediately. DO NOT induce vomiting.

**THIS PRODUCT IS FOR  
PROFESSIONAL USE ONLY.**

**KEEP THIS PRODUCT OUT OF THE  
REACH OF CHILDREN.**

**WARRANTY:** The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control.

**TRIANGLE COATINGS, INC.** 1930 Fairway Drive, San Leandro, CA 94577-5631 • Tel: 510-895-8000 • Fax: 510-895-8800 • [www.tricoat.com](http://www.tricoat.com)